

MATERIAL SAFETY DATA SHEET

BEST-O-FINISH

This MSDS complies with ANSI Z400.1-2004

| 01 - PRODUCT AND COMPANY IDENTIFICATION | | | | |
|---|---|----------------------------------|---|-----------------------------------|
| Manufactured by: | Bestway Products Company | | Trade name (used on label): Best-0-Finish | |
| Address: | 333 West 700 South Salt Lake City, UT. 84101 | | Intended use: Buffable floor finish | |
| PH: (801)328-4818 | FAX: (801)328-9080 | EMAIL:MSDS@BESTWAY.PRO | | |
| MSDS prepared by: C. Beckstead | EMERGENCY REPOSE NUMBER: (CHEM-TEL) 1(800)255-3924 | | Prepared:01/27/11 @ 09:40:59 AM | MSDS number: 01 Revision: 2 |
| 02 - HAZARD IDENTIFICATION | | | | |
| PRIMARY ROUTES OF ENTRY: [X] INHALATION [X] INGESTION [] SKIN ABSORPTION [X] EYE [] NOT HAZARDOUS | | | | |
| ACUTE EFFECTS: | | | | |
| Inhalation: Excessive inhalation of vapors can cause nasal & respiratory irritation, dizziness, weakness, nausea, headache, possible unconsciousness or asphyxiation. | | | | |
| Eye Contact: Possible irritation. Skin Contact: Possible irritation. Ingestion: Possible gastrointestinal irritation. | | | | |
| 03 - COMPOSITION/INFORMATION ON INGREDIENTS | | | | |
| (Hazardous Components 1% or greater; Carcinogens 0.1% or greater) | | | | |
| | CAS NUMBER | OSHA PEL | LC50 | % |
| Glycol Ether D.E. | 111-90-0 | 100 ppm | N/D | |
| Dibutyl Phthlate | 84-74-2 | 5 mg/m(3) | N/D | |
| Tributoxyethylphosphate | 71-58-3 | N/E | N/D | |
| Formaldehyde 37%** | 50-0-0 | .75ppm | N/D | 0.17% |
| 04 - FIRST AID MEASURES | | | | |
| Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention. Skin Contact: Wash with soap and water. | | | | |
| Inhalation: Remove to fresh air. Ingestion: Call poison control or Chem-Tel @ 1-800-255-3924 | | | | |
| Notes to physician: | | | | |
| 05 - FIRE FIGHTING MEASURES | | | | |
| Flash Point (method determined): N/A Auto Ignition Temperature: N/A FLAMMABILITY as per USA FLAME PROJECTION TEST :N/A | | | | |
| Flammability Limits in Air by % in SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus. Use | | | | |
| Volume: % LEL: N/A % UEL: N/A water fog to cool containers to prevent rupturing & exploding containers. | | | | |
| Unusual Fire & Explosion Hazards: None EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water. | | | | |
| 06 - ACCIDENTAL RELEASE MEASURES | | | | |
| Small Spills: Pick up with mop or wet vac and wash away with water. Ventilate area of spill or leak. | | | | |
| Large Spills: Dike area. Keep spill and cleaning runoffs out of municipal storm drains and open bodies of water. | | | | |
| Transfer liquids and diking material to separate suitable containers for recovery or disposal. | | | | |
| 07 - HANDLING AND STORAGE | | | | |
| Handling: Empty containers should be triple rinsed and can be refilled with a similar material. Please recycle! | | | | |
| Storage: Freezing of product may rupture container. Shelf life is best retained by storing at 45 to 100 degrees F. | | | | |
| 08 - EXPOSURE CONTROLS AND PERSONAL PROTECTION | | | | |
| Respiratory Protection (specify type): None normally required. | | | | |
| Protective Gloves: Rubber or latex if desired. Eye Protection: Safety glasses recommended. | | | | |
| Ventilation Requirements: Mechanical if necessary to keep vapor concentration below TLV. | | | | |
| Other Protective Clothing & Equipment: None required when using according to label instructions. | | | | |
| Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing. | | | | |
| 09 - PHYSICAL AND CHEMICAL PROPERTIES | | | | |
| Physical State: Liquid. | | Boiling point: 212 f | | Vapor pressure: Unknown. |
| Odor/Appearance: Light ammonia/white. | | Freezing point: 35 f | | Vapor density: Unknown. |
| PH: 9.5 | | Evaporation rate: > ethyl ether. | | Liquid density: Unknown. |
| Specific Gravity: 1.03 | | % Volatile: 78% | | % Soluble in water: 100% |
| 10 - STABILITY AND REACTIVITY | | | | |
| Chemical stability: Stable. Hazardous decomposition: No data available. | | | | |
| Hazardous polymerization: Will not occur. Incompatibility: Avoid contact with: Strong oxidizing agents. | | | | |
| 11 - TOXICOLOGICAL INFORMATION | | | | |
| CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) When used as directed, no adverse effects anticipated from available information. | | | | |
| Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions. | | | | |
| 12 - ECOLOGICAL INFORMATION | | | | |
| Aquatic toxicity: No ecological information available at this time. | | | | |
| Environmental fate: This product is biodegradable. | | | | |
| 13 - DISPOSAL CONSIDERATIONS | | | | |
| Dispose of in accordance with all applicable local, state and federal laws. Buyer assumes all risk and liability associated with disposal of this product, original and secondary containers. | | | | |
| 14 - TRANSPORT INFORMATION | | | | |
| DOT CLASSIFICATION-(49 cfr 172.101) Liquid floor wax and polish. | | | | |
| 15 - REGULATORY INFORMATION | | | | |
| FEDERAL: Not determined at this time. | | | | |
| STATE: Not determined at this time. | | | | |
| LOCAL: Not determined at this time. | | | | |
| 16 - OTHER INFORMATION | | | | |
| NFPA Rating: | Health-1 | Flammability-0 | Reactivity-0 | Special Hazard - NONE |
| HMIS Rating: | Health-1 | Flammability-0 | Reactivity-0 | Personal Protection Equipment - A |
| We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. | | | | |
| ** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only | | | | |