



## **FOUNDATION SEALER/BASECOAT**

### **DESCRIPTION:**

FOUNDATION is an acrylic sealer which is recommended for sealing porous surfaces. Provides a strong foundation for longer wear properties. Will not discolor even the lightest floor. Excellent soil, abrasion and detergent resistance. The perfect foundation for waxes and synthetic resin emulsion finishes. Delivers optimum protection for flooring subjected to heavy traffic.

### **FEATURES AND BENEFITS:**

- Protects floors from dirt spills and abrasion that comes from heavy traffic.
- Fast drying
- Will not yellow with age.
- Excellent water and detergent resistance.
- Provides an excellent base for high speed/ultra high speed finishes.

### **APPLICATION:**

For use on all types of floors including : vinyl asbestos, rubber, asphalt, grease-proof asphalt tile, linoleum, terrazzo, concrete, slate and quarry tile.

This product should be applied at the rate of 1500-2000 sq. ft./gl.

See product label for additional application instructions.

### **TYPICAL PROPERTIES:**

|                      |                              |
|----------------------|------------------------------|
| Appearance:          | Low viscosity, milky liquid. |
| Odor:                | Mild ammonia odor            |
| Solubility in water: | Miscible                     |
| pH:                  | 9.5                          |

### **STORAGE RECOMMENDATION:**

- Store at temperatures below 110°F and above 40°F.
- Keep containers tightly closed and upright to prevent leakage.
- 1 year recommended shelf life.

### **STANDARD PACKAGING:**

- 1 gallon (8.5 lb.) plastic bottle with handle.
- 5 gallon (45 lb.) plastic pail with NVRI spout.
- 55 gallon (500 lb.) L-1 poly drum.

### **WASTE DISPOSAL:**

- Dispose of liquid and solid waste in accordance with local, state, and federal regulations.
- Containers are made from HDPE and are recyclable. Contact an accountable recycling company.

### **SAFETY:**

- Consult Material Safety Data Sheet before using this product.
- Plastic gloves and eye protection should be used when handling this product.