



RESTORATION FINISH RESTORER

DESCRIPTION:

Heat generated by ultra high speed buffing floor machines creates a unique thermal chemical reaction between BESTWAY RESTORATION's thermal reactive components and a thermoplastic floor finish. The heat activated ingredients become a part of the original seal and finish, resulting in a hard, ultra brilliant surface.

FEATURES AND BENEFITS:

- Restores gloss
- Excellent Durability.
- Will not yellow with age.
- Excellent water and detergent resistance.

APPLICATION:

For use on all types of floors including vinyl, vinyl asbestos, rubber, terrazzo, quarry and ceramic tile, slate, sealed wood, cork and concrete.

This product should be diluted 1 part to 2 parts water.

See product label for additional application instructions.

TYPICAL PROPERTIES:

Appearance:	Low viscosity, milky liquid.
Odor:	Mild ammonia odor
Solubility in water:	Miscible
pH Concentrate:	9.5

STORAGE RECOMMENDATION:

- Store at temperatures below 110°F and above 40°F.
- Keep containers tightly closed and upright to prevent leakage.
- 1 year shelf life.

STANDARD PACKAGING:

- 1 gallon (8.5 lb.) plastic bottle with handle.
- 5 gallon (45 lb.) plastic pail with NVRI spout.
- 55 gallon (500 lb.) L-1 poly drum.

WASTE DISPOSAL:

- Dispose of liquid and solid waste in accordance with local, state, and federal regulations.
- Containers are made from HDPE and are recyclable. Contact an accountable recycling company.

SAFETY:

- Consult Material Safety Data Sheet before using this product.
- Plastic gloves and eye protection should be used when handling this product.